

Low Profile Rotary Actuator

The Low Profile Rotary Actuator from ITT Aerospace Controls is a compact design which allows for applications in areas where height restrictions prevent the incorporation of “chimney” style actuators.

These units feature a worm gear drive system which prevents back-driving while allowing for high torque loads. The Low Profile Actuator also uses a permanent magnet motor with an iron-less rotor. The result is high efficiency, longer life and increase reliability. Limit switches are operated directly by the output shaft. All components are housed within an environmentally sealed aluminum or composite enclosure.

Features

- Permanent magnet motors
- Worm gear drive
- Operates from 28 VDC or 155 VAC 400 Hz.
- Position indication or manual override
- Environmentally sealed enclosure
- Torque ratings to 300 in./lbs.
- Endurance life to 500,000 cycles
- Interface/mounting versatility
- Electrical fail-safe provisions
- Modulating option available

Typical Applications

- Fuel valves
- Hydraulic valves
- Cooling/heating valves
- Door actuation
- Dump valves
- Potable/waste water
- Utility valves



Low Profile Rotary Actuator

Typical Specifications

| | |
|----------------------------|---------------------------------------------------------------------------------------|
| Type : | Rotary, 90° permanent magnet motor |
| Power: | 28 VDC |
| Torque Load: | 0-35 in-lbs. (0 - 4.0 N-m) |
| Operating Time: | .5 to 1.0 Sec/90° |
| Life Cycles: | 250,000 at rated torque |
| Weight: | 0.97 lbs. (440 gm) with manual override 0.79 lbs. (360 gm) without manual override |
| EMI Filtration: | RTCA/DO-160C/MIL-STD-461C |
| Electrical Connector: | As required |
| Dielectric Strength: | 1500 VAC |
| Ambient Temperature Range: | -70°F to 275°F (-57°C to 135°C) |

Basic Dimensions

